

## ATMIS-6408PI



**PRODUCT OVERVIEW:** - **ATMIS-6408PI** is Managed Ring Industrial-grade PoE Switches, with 8\*10/100/1000 Mbps adaptive RJ45 port and 4\*1000Mbps SFP optical fiber module extension slot. All 8 RJ45 ports support PoE power supply, with a maximum of 90W for each port. Support static routing functions, provide perfect security, QoS, and plenty of VLAN functions has ring network function, can form a ring network, and Switch between by hand in hand form a ring network topology, the redundancy, high reliability characteristics can make in a ring online link disconnected all the way, will not affect the forwarding of data on the network.

The device adopts no fan, low power consumption design, has the advantages of easy to use, compact and beautiful, simple installation. The product is designed to meet Ethernet standards, with lightning protection, static protection mechanism, operating temperature range of -40°C to 75°C, stable performance, safety and reliability, can be widely used in intelligent transportation, telecommunications, and security, financial securities, customs and other broadband data transmission fields, enclosed IP65 Rating

### PRODUCT FEATURES:-

- Supports IEEE802.3, IEEE802.3u, IEEE802.3ab, IEEE802.3z, and IEEE802.3x standards;
- PoE supports IEEE 802.3af/at/bt standards and provides a maximum output of 90W for each port;
- Supports IEEE802.3x full-duplex flow control and Backpressure half-duplex flow control;
- Panel indicators monitor working status and assist in fault analysis;
- High energy aluminum alloy roof heat conduction groove design;
- Supports one-click ring network and one-click storm suppression, featuring redundancy and high reliability;
- High reliability design, supporting traditional STP/MSTP/RSTP layer 2 link protection technology;
- Support static convergence and dynamic convergence (LACP) 2 convergence modes, effectively increase the link bandwidth, improve the reliability of the link, and at the same time can achieve load balancing, link backup;
- Flexible and convenient management and maintenance Supports various management modes, such as Console, Telnet, and SSH;
- Supports WEB management, which is simple and efficient, and facilitates installation and debugging by engineering and maintenance personnel. Supports file upload and download management through TFTP;

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone : +91 120 4109590, +91 98716 50366

E-mail : [Info@andatelecom.com](mailto:Info@andatelecom.com)

URL : [www.andatelecom.com](http://www.andatelecom.com)

## PRODUCT SPECIFICATION:-

<b>Model</b>	ATMIS-6408PI
<b>Standard</b>	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.1X, IEEE802.1q, IEEE 802.1p, IEEE 802.1d, IEEE 802.1w, IEEE 802.3ad, IEEE802.3af, IEEE802.3at
<b>Interface</b>	8*10/100/1000Mbps RJ45 Ports 4*1000Mbps SFP Slots 1 Console Port
<b>Indicator</b>	PWR, LNK/ACT, PoE, SYS
<b>Network Media</b>	10BASE-T: UTP category 3,4,5 cable (≤100m) 100BASE-TX: UTP category 5, 5e cable (≤100m) 1000BASE-T: UTP category 5e, 5 cable (≤100m) 1000BASE-X: MMF, SMF
<b>MAC Address Table</b>	8K, Auto-learning, Auto-aging
<b>Jumbo Frame</b>	9216Bytes
<b>Packet Buffer</b>	4.1Mbit
<b>Transfer Mode</b>	Store-and-forward
<b>Packet Forward Speed</b>	17.5Mpps
<b>Switching Capacity</b>	24Gbps
<b>Dimensions(L*W*H)</b>	110*90*46mm
<b>Fan Quantity</b>	Fanless
<b>PoE Power Budget</b>	240W
<b>PoE Port</b>	Port1~8
<b>PoE Power on RJ45</b>	Mode A 1/2 (-), 3/6 (+)
<b>PoE Power Output</b>	90W (MAX)
<b>Green Energy Saving</b>	IEEE 802.3az
<b>Input Power Supply</b>	Dual DC: 48-57V
<b>Operating Temperature</b>	-40°C ~ 75 °C
<b>Storage Temperature</b>	-40 °C ~ 80 °C
<b>Operating Humidity</b>	5% ~ 95% non-condensing
<b>Storage Humidity</b>	0% ~ 95% non-condensing
<b>Surge Protection</b>	Differential mode ±2KV Common mode ±6KV
<b>MTBF</b>	>600000 hour

<b>Electrostatic Standard</b>	Contact ±6KV, Air ±8KV
-------------------------------	------------------------

## SOFTWARE SPECIFICATION:-

<b>L2 Features</b>	<b>MAC Address Table</b>	MAC Address Size
		MAC Aging Time
		MAC Filter
		MAC Notification
	<b>Basic Management</b>	Console/Telnet/SSH
		Http/Https, SSL/TLS
		FTP/TFTP
		Syslog
		SNMP(v1/v2c/v3), SNMP Trap
		SNTP/NTP
		CPU protect
		Software/Hardware watchdog
		Firmware Upgrade/Backup
		Ping/Traceroute
	<b>Port Config</b>	Bandwidth Control
		Flow Control
		EEE
		MTU
		CFM (802.1ag)
		EFM OAM (802.3ah)
		DDM
		Storm Control
		Port Isolation
		Port Security
	<b>Discovery</b>	LLDP (802.1ab)
		LLDP-MED
	<b>Link Aggregation</b>	Static
		LACP (802.3ad)
		Load Balance(src-mac/dst-mac/src-ip/dst-ip)
		Max groups and ports per group
	<b>VLAN</b>	VLAN (802.1Q 4K)
		Access/Trunk/Hybrid
		Private VLAN
		VLAN Filter
		MAC-based VLAN
		Protocol-based VLAN
		IP Subnet-based VLAN
		Voice VLAN
		GVRP/GMRP
	<b>Network Loop Detection</b>	Loopback Detection
		ERPS
	<b>Spanning Tree</b>	STP/RSTP/MSTP
		MSTP Support 64 instance

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone : +91 120 4109590, +91 98716 50366

E-mail : [Info@andatelecom.com](mailto:Info@andatelecom.com)

URL : [www.andatelecom.com](http://www.andatelecom.com)

	<b>ARP</b>	BPDU Guard/Root Guard/BPDU Tunnel
		Static ARP
		Dynamic ARP Inspection
		ARP Quantity Control

<b>IPv4 Related Function</b>	<b>ICMP</b>	Anti ICMP Attack
		ICMP Rate Limit
		ICMP Unreachable Drop
	<b>IP Forward</b>	Static Route
		Route Aggregation
	<b>Control Multicast</b>	DCSCM
	<b>Multicast VALN</b>	Multicast VALN
	<b>IGMP</b>	IGMP SNOOPING V1/V2/V3
		Fast Leave
		IGMP Proxy
	<b>DHCP</b>	DHCP Server
		DHCP Client/BOOTP
		DHCP Relay
		DHCP Snooping
		DHCP Option 82/43/60/61/67
<b>IPv6 Related Function</b>	<b>IPv6 Basic</b>	IPv6 ND Snooping
	<b>DHCPv6</b>	DHCPv6 Server
		DHCPv6 Relay
		DHCPv6 Snooping
		IPv6 SAVI
		Security RA
	<b>IPv6 Unicast Routing</b>	Static Route
	<b>IPv6 Multicast Routing</b>	MLD v1/V2 Snooping
	<b>IPv6 Features</b>	SNMP over IPv6 Support
		HTTP over IPv6 Support
		SSH over IPv6 Support
		DNS over IPv6 Support
		IPv6 ping/traceroute Support
		IPv6 Telnet Support
		IPv6 Radius+ Support
		IPv6 Tacacs+ Support
		IPv6 SNTNTP Support
		IPv6 FTP/TFTP Support
		IPv6 IPsec Support
		IPv6 ACL
	<b>Basic</b>	Trust COS/DSCP
		Trust Port
		SP
	<b>Scheduling</b>	WRR
		WDRR

QoS(Quality Of Service)	PolicyMap Stream	Based on VLAN
		Based on COS/DSCP
		Aggregate PolicyMap
		Ingress PolicyMap
	Policing	CAR Stream Shaping (leak algorithm)
		Ingress Policing
	Rewrite	COS/802.1p Priority
		IP Precedence
		IPv4 DSCP/IPv6 DSCP
		drop-precedence

	Queuing	internal-priority
		Ingress/Egress Rewrite
		DSCP to DSCP mapping
		DSCP to DP mapping
		DSCP to Queue mapping
		COS to DP mapping
		COS to Queue mapping
ACL	IP-ACL	SIP/DIP
		IP Protocol
		IP Priority(DSCP,TOS, Precedence)
		TCP,UDP src,dst Port
	MAC-ACL	SRC/DST MAC
		VLAN
		COS
		Tag/Untag
	IP-MAC ACL	MAC-ACL and IP-ACL
	User-defined ACL	Base on user defined profile
Security	802.1x	Based on time period ACL
		ACL on VLAN
		Based on ACL Stream
		Port Based Authentication
	MAB	Support EAPoR
		MAC-based Authentication
		Guest VLAN
		Based on Port Authentication
	MAC Address Count Limit	Based on MAC Authentication
		Based on Port
	IP Address Count Limit	Based on VLAN
		Based on Port
	Access Management	Based on VLAN
		Based on source mac and IP address
	Deny DoS Attack	Based on TCP Flag
		TCP Flagment
		IP Segment
		ICMP

	<b>TACACS+</b>	Standard Support
	<b>Radius</b>	Standard Support Client, Support MD5
	<b>SSL</b>	Openssl 1.1.0
<b>Redundancy Related Function</b>	<b>MRPP</b>	Compatible ERRP
	<b>ULPP</b>	Uplink Protection Protocol Smart Link/Monitor Link
	<b>ULSM</b>	Uplink State Monitor
<b>Flow Monitor Function</b>	<b>Mirror</b>	Support one-to-one, multi to one
		Port-based mirror, support ingress, egress, and both
		CPU based mirror
		Flow-based mirror

		RSPAN
<b>PoE</b>	<b>PoE Management</b>	ON/OFF Config
		Alive Checking for PD
		7/24 On/Off Scheduling

#### ORDERING INFORMATION:-

Model	Product Information
<b>ATMIS-6408PI</b>	8-Port Gigabit +4G SFP Industrial Fast Ring Managed PoE Switch, Total PoE budget 240watt ,2*DC Powers socket

#### ORDERING INFORMATION: -

<p>Anda Telecom Pvt. Ltd. Registered Office: PLOT NO 38, BLOCK E, -, Sector 6, Noida, Gautambuddha Nagar, Uttar Pradesh, 201301</p> <p>India.</p>	  	<p><a href="https://andatelecom.com/">https://andatelecom.com/</a></p> <p>+91 120 4109590 + 91 98716 50366</p> <p><a href="mailto:info@andatelecomindia.com">info@andatelecomindia.com</a></p>
---	---	--