



# AT-S3900-48T6X



Varied Service Characteristics  
Versatile IPv6 Solution  
Complete Security Mechanism



Carrier-Level High Reliability  
Full Layer-3 Functions



Advanced Hardware Architecture and Industry-leading Port Density



Supports Maximum 48 GE Ports and 6 10GE SFP+ Uplink Ports

## Product Overview

ANDATELECOM, AT- S3900 Series is a new generation of aggregation 10G switches .It is targeted at the IP MAN (metropolitan area network), campus networks and enterprise networks. It is developed on the basis of high-performance hardware and ANDAROS software platform with ANDA own independent intellectual property rights. It supports multiple services like IPv6, VPN and network security based on L2/L3/L4 wire-speed switching service. It also supports non stop upgrade, continuous forwarding, graceful restarting and redundancy protection.

ANDA S3900 Series model Has : , A T-S3900-48T6X. It supports up to 48 gigabit ports and 6 10GE ports.

## Innovative Virtual Cluster Switching Technique

(ANDA TELECOM Virtual Switch System):

It's makes full use of each link in the physical devices, which avoids STP blocking the link and protects the original link to the maximum extent.

### Improved Performance:

Virtualize multiple physical devices into one. The performance, reliability and management of the virtualsystem are superior to the physical ones.

### High Reliability:

Based on the advanced distribution mechanism and efficient cross-physical link aggregation link function, the logiccontrol plane, service control plane and service data plane are separated. Thus, the device can support continuous layer-3 routing forwarding, avoiding service interruption as a result of a single point of failure.

### Easy Management:

It's realizes single IP management, greatly improving the networking efficiency and lowering the operating cost.

ANDA Telecom Pvt. Ltd.

Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA  
Phone : +91 11 41323629, +91 95 302 57173

E-mail : [Info@andatelecomindia.com](mailto:Info@andatelecomindia.com)

URL : [www.andatelecomindia.com](http://www.andatelecomindia.com)

## Product Characteristics

### Carrier-Level QoS Policies

Supports priority retagging and complicated flow classification based on VLAN, MAC, source address, destination address, IP or priority to better streamline carrier's services. Supports flexible bandwidth control policies and supports port-/flow-based flow limit, and ensuring the line speed forwarding of each port to make sure the high quality of video, audio and data services. Supports 8 priority queues by each port. Supports multiple queueschedule algorithms such as SP, WRR, and SP+WRR.

### Varied Service Characteristics

Supports layer-2 and layer-3 multicast routing protocol, which enable the device can access to IPTV, HD video surveillance and HD video conference. Supports layer-3 routing protocol and super-large routing table capacity, which enables the device is available in large campus networks, enterprise networks and industry networks.

### Versatile IPv6 Solution

Supports the IPv6 protocol suite, IPv6 neighbor discovery, ICMPv6, path MTU discovery, DHCPv6, etc. Supports Ping, Trace route, Telnet, SSH, ACL. Supports MLD, MLD Snooping, IPv6 static routing, RIPng, OSPFv3 and BGP4+, etc. Supports IPv6 tunnel: manual tunnel, automatic tunnel, GRE tunnel, 6to4, ISATAP Supports IPv4 transits to IPv6: IPv6 manual tunnel, automatic tunnel, 6 to 4 tunnel, ISATAP tunnel.

### Industrial Ethernet Ring with Zero Delay and Zero Packet Loss

Supports industry-level EAPS and ERPS, and their protection recovery time is less than 50ms. Their high reliability is represented by the null packet loss, which has been proved by many years of application in the Grid, rail transportation and defense systems.

### Complete Security Mechanism

Equipment-Level Security: The advanced hardware infrastructure design realizes the level-based packetschedule and packet protection, prevents DoS-/TCP-related SYN Flood, UDP Flood, Broadcast Storm or large traffic attacks, and supports level-based command line protection, endowing different levels of users with different management permissions. Security Authentication Mechanism: IEEE 802.1x, Radius and ANDA

Tacacs+ Enhanced ServiceSecurity Mechanism: supports the plaintext or MD5 authentication of relevant routing protocol, URPF, deep inspection of hardware packet, control packet and data packet and filtering technology.

### Innovative Energy-Saving Design

Intelligent power management: The power system of S3900 series supports real-time monitoring the device and the slow-start. It is also power-saving. Intelligent fan management system: The fan system of S3900 Series supports automatic speed regulation, which efficiently slow the fan speed and mitigate the noise. Complies with the international standard IEEE 802.3a

### Flexible and Convenient Management and Maintenance

Supports management modes such as the console port, Telnet, SSH, etc. Supports the WEB management mode, which is easy and efficient so that it makes installation and debugging convenient. Supports TFTP-patterned file upload/download management. Supports ISSU (In-Service Software Upgrade). Supportts SNMP and ANDA NMS smart network management platform to realize automatic equipment discovery, network topology management, equipment configuration management, performance data statistics and analysis and trouble management.

# Model AT-S3900-48T6X

- 1. 48 GE TX Ports (48T6X)
- 2. 6 10G/GE SFP+PORTS



## Specifications

Item	AT-S3900-48T6X
GE Interface	TX 48
SFP 10GE Interface	6 10GE/GE
Console	1 RJ45 Port
Backplane	216 Gbps
Forwarding rate	162 Mpps
<b>Physical Specifications</b>	
Chassis Dimensions (WxDxH mm)	440x350x44
Package Dimensions (WxDxH mm)	576x448x94
<b>Power</b>	
Power supply AC: 100V-240V (hot-swap) 50Hz±10%	75W
Total output BTU (1000BTU/H=293W)	255 . 97
Noise@25°C(dBA)	45
MTBF(H)	>200,000
Forwarding mode	Store-forward
Flash (MB)	16
DRAM (MB)	512
MAC	32K
Buffer size(MB)	2
Jumbo frame	9K
Routing table IPv4	12K
IPv6	6K
ARP table IPv4	12K
IPv6	2K
Total SVI	1K



## Features

### VLAN

- 4K Active VLAN,
- QinQ & Selective QinQ,
- GVRP,
- Voice-VLAN

### Spanning Tree

- 802.1D (STP),
- 802.1W (RSTP) and 802.1S (MSTP) BPDU guard,
- root guard and loopback guard

### Multicast

- PIM-SM, PIM-DM, IGMP v1/v2/v3,
- IGMP Snooping, IGMP Fast Leave,
- MVR, IGMP filter

### IPv4

- Static routing, RIP v1/v2, OSPF, BGP, PBR, ECMP
- BFD for OSPF, BGP

### DHCP

- DHCP server/relay/client
- DHCP snooping/option82

### MPLS

- Multi-VRF

### IPv6

- ICMPv6, DHCPv6, ACLv6 and IPv6 Telnet
- IPv6 neighbor discovery, Path MTU discovery
- MLD V1/V2, MLD snooping
- IPv6 Static Routing, RIPng, OSPFv3, BGP4+
- Manual tunnel, ISATAP tunnel, 6 to 4 tunnel

### QoS

- CAR, HQoS, MAC/IP/TCP/UDP/VLAN/ COS/DSCP/TOS based QoS, 802.1P/ DSCP priority re-labeling, SP, WRR, and "SP+WRR", Tail-Drop, WRED, flow monitoring and traffic shaping

### Security

- Port isolation, Port security, and "IP+ MAC+port" binding, MAC sticky, DAI & IP source guard, PPPoE+
- IEEE 802.1x, Radius and ANDA Tacacs+
- L2/L3/L4 ACL flow identification and filtration Anti-attack from DDoS, TCP's SYN Flood, UDP Flood, etc.
- Broadcast/multicast/unknown unicast storm-control
- MD5, SHA-256, RSA-1024, AES256, etc.

### Reliability

- Static/LACP link aggregation, Interface backup
- IT,S virtual-stacking
- EAPS and ERPS
- URPF, LLDP
- ISSU
- VRRP
- 1+1 power backup

### Management

- Console, Telnet, SSH v1/2, HTTP, HTTPS
- SNMP v1/v2/v3, RMON
- TFTP, FTP, SFTP
- NTP, SPAN, RSPAN
- sFlow

### Accessories

- Power cord, rack mount kits, console cable

### Environment

- Operating temperature/humidity: 0°C -50°C , 10%-90% non-condensing
- Storage temperature/humidity: -20°C -70°C , 5%-95% non-condensing

### Certification

- CE, FCC, ROHS

## Ordering Information

Item	Description
<b>S3900 series switch</b>	
<b>ATS-3900-48T6X</b>	Ethernet routing switch with 48 GE and 6 10GE ports (1 RJ45 console port, 48 GE TX ports, 6 10GE/GE SFP+ ports; 2 power slots with 1 hot-swap AC220V power supply; the cooling fan, 1U, standard 19-inch rack-mounted installation)

## Ordering Information

Item	Description
<b>S3900 series switch</b>	
<b>S3900 Series Non-POE Power Modules</b>	
<b>PWR-75-AC</b>	Hot-swap AC Power for AT-S3900-48T6X Series (75W max, AC100~240V input)
<b>PWR-75-DC</b>	Hot-swap DC Power for S3900-48T6X Series (75W max, DC- 36~-72V input)