

ATS2528P Series All Gigabit Security POE Switch

ATS2528P Series all GE POE switches is a new generation of intelligent carrier-grade GE switches. They are applied into 802.11n platform.

As a leading high-performing POE switches, ATS2528P series switches provide large capacity, high-density GE ports to fully meet customer's demand with cost-effective GE access/aggregation. For enterprise network users and carrier about WLAN,WIFI,FTTH, security monitoring and many other scenarios, ATS2528P POE switches provide convenient maintenance methods to reduce network planning, construction and maintenance pressure in order to build future-oriented enterprise IT network. ATS2528P POE switches satisfy IEEE standard of 802.3af and 802.3at. The maximum power consumption of each port is 32W, the whole power consumption can reach 370W.

ATS2528P-28PC



- 24*10/100/1000Base-T with POE power supply
- 4*100/1000M BaseX SFP
- 16K Jumbo, 8K MAC address, 4K VLAN, QinQ
- 256ACL with IP+MAC+Port+VLAN binding
- Full-loaded power-consumption< 30W (without POE supply)
- POE supply satisfy 802.3af and 802.3at
- Max power consumption supply of single port is 32W
- Maximum POE power consumption is 400W
- 440mm(W)*359mm(D)*44mm (H)

Product Specifications:

Item	ATS2528P-28PC
Backplane capacity	68Gbps
Interface switching capacity	56Gbps
Forwarding capacity	41.7Mpps
Memory and flash	64MB SDRAM memory and 8MB flash
Lightning Protection	± 4 kV for Ethernet Port
Ethernet Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab , IEEE 802.3z, IEEE 802.3x, IEEE 802.1X, IEEE 802.1q , IEEE 802.1p, IEEE 802.1d , IEEE 802.1w, IEEE 802.3ad

ANDA Telecom Pvt. Ltd.

ISO 9001:2000 Certified Company

Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone : +91 11 41323629, +91 93 502 57173

E-mail : Info@andatelecomindia.com

URL : www.andatelecomindia.com



ISO 9001:2000 Certified Company

POE features	Satisfy 802.3af and 802.3at standard, max power consumption supply of single port is 32W			
Power consumption	Full-loaded ≤20W (without POE)	Full-loaded ≤25W (without POE)	Full-loaded ≤28W (without POE)	Full-loaded ≤30W (without POE)
	Idle ≤16W	Idle ≤18W	Idle ≤20W	Idle ≤22W
Dimensions (width x depth x height))	335mm×44mm×220mm	335mm×44mm×220mm	440mm*44mm*359mm	440mm*44mm*359mm
Weight (Full-loaded)	≤4.5KG	≤4.5KG	≤4.5KG	≤5KG
Environmental requirements	Operating Temperature: -15°C~55°C Storage Temperature: -40°C~70°C Relative humidity: 10%~90%, non-condensing			
Power	Power Supply : 170-240 Volts at 50 ± 2 Hz.			

Business Features:

Item		ATS2528P
L2 features	MAC	12K MAC address MAC Black Hole Port MAC Limit
	VLAN	4K VLAN entries Port based QinQ PVLAN to realize port isolation and saving public-vlan resources GVRP
	Spanning tree	STP/RSTP/MSTP Remote Loop back Guard BPDU Guard, Root Guard (STRG), Loop back Guard
	Port	Bidirectional bandwidth control, configure entry/exit and the smallest 64K control particle Static and LACP LLDP/LLDP MED(802.3ab) Port- mirroring of 1:1 or N:1,
L3	IP	Static Route, RIPV1, V2, OSPF, 512 Routing Table, DHCP Server/Client/Relay
Security features	User's security	ARP anti-Flooding, configure ARP traffic safety threshold and inhibition ARP packet ARP anti-Spoofing, configure ARP inner and outer MAC check and static ARP checklist

ANDA Telecom Pvt. Ltd.

ISO 9001:2000 Certified Company

Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone : +91 11 41323629, +91 93 502 57173

E-mail : Info@andatelecomindia.com

URL : www.andatelecomindia.com



ISO 9001:2000 Certified Company

		<p>and drop / flood action, (err disable) to automatically Link re-enable IP+MAC+port+VLAN binding manually Port Isolation, configure hardware isolation of each port Bind MAC address to port and MAC address filtration on port IEEE 802.1x and AAA/Radius authentication,</p>
	Device security	<p>Anti-DOS attack SSHv2 Secure Shell SNMP v3 encryption Telnet based on Security IP Prevent unauthorized user, SYN Flood, UDP flood, Broadcast stream and large traffic attack</p>
	Network security	<p>One button binding based on dynamic ARP table Manual binding parameter of IP 、 VLAN ID、 MAC and port , LLDP/LLDP MED(802.3ab) L2-L7 ACL flow filtration Auto-shutdown port in storm Update user's location through DHCP Option82 and PPP</p>
Service features	ACL	<p>Activate standard and extended ACL Time Range ACL strategy Flow classification based on SMAC、 DMAC、 VLAN、 SIP、 DIP、 IP IP(IPv4/IPv6) 、 TCP/UDP port num、 protocol type etc. Packet filtration of L2~L7 IP header with 80bytes</p>
	QoS	<p>Rate-limit to packet sending/receiving speed of port or self-defined flow and provide general flow monitor and two-speed tri-color monitor of self-defined flow Packet mirror and redirection of interface and self-defined flow Supports Priority remark to port or self-defined flow and provide 802.1P, DSCP priority and Remark Super queue scheduler based on port and self-defined flow. Each port/ flow supports 8 priority queues and scheduler of SP, WRR and SP+WRR, Tail drop, WRED, Flow Monitoring and Traffic shaping</p>
	Multicast	<p>IGMPv1/v2/v3 Snooping IGMP Filter MVR multicast VLAN register and cross VLAN multicast replication IGMP Fast leave IGMP Proxy</p>
Reliability	Loop protection	EAPS and GERP , Loopback-detection
	Link protection	<p>FlexLink RSTP/MSTP LACP</p>
	Device protection	Backup of host program and configuration files

ANDA Telecom Pvt. Ltd.

ISO 9001:2000 Certified Company

Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone : +91 11 41323629, +91 93 502 57173

E-mail : Info@andatelecomindia.com

URL : www.andatelecomindia.com



ISO 9001:2000 Certified Company

Maintenance	Network maintenance	Port real-time, utilization and transmit/receive statistic based on CLI Port real-time, utilization and transmit/receive statistic based on CLI 802.3ah Ethernet OAM Syslog and RFC 3164 BSD syslog Protocol Ping and Traceroute
	Device management	CLI, Console port, Telnet and WEB SNMPv1/v2/v3 RMON (Remote Monitoring)1,2,3,9 group MIB NTP

Purchase Information:

Product name	Product Description
ATS-2528P	POE, 24*10/100/1000BaseT, 4*GE(1000Base-X SFP)

ANDA Telecom Pvt. Ltd.
 ISO 9001:2000 Certified Company
Registered office : E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA
Phone : +91 11 41323629, +91 93 502 57173
E-mail : Info@andatelecomindia.com URL : www.andatelecomindia.com