

ATS - 2900 - 3200



PRODUCT OVERVIEW: -

ANDA TELECOM is a next-generation intelligent gigabit access switch crafted for carrier IP MAN and enterprise networks. Built on cutting-edge high-performance hardware and the ANDA platform, it features ACL, QinQ, and QoS capabilities. Its straightforward management mode and versatile installation options are designed to handle even the most complex scenarios.

ANDA TELECOM switches support the carrier-level Ethernet ring protection protocol with a recovery time of less than 50ms, along with STP/RSTP/MSTP, backup uplink ports, and LACP link aggregation to meet carriers' high reliability requirements. These switches offer robust ACL capabilities to access and control L2-L7 data based on physical ports, providing carriers with flexible and diverse policy control methods. ANDA TELECOM switches also support In-Service Software Upgrade (ISSU) to ensure continuous data forwarding during system upgrades. Additionally, they support various L2 multicast functions such as IGMP snooping, fast-leave, and MVR to fully satisfy the operational needs of carrier IPTV.

PRODUCT CHARACTERISTIC: -

IPV6

The ANDA TELECOM switch series supports the full IPv6 protocol suite, including IPv6 neighbour discovery, ICMPv6, and Path MTU discovery. It also provides IPv6-compatible Ping, Traceroute, Telnet, SSH, and ACL functions, fulfilling the management and service control requirements of IPv6 networks.

Security

Equipment-Level Security: The advanced hardware design of ANDA TELECOM switches features level-based packet scheduling and protection, defending against DoS and TCP-related SYN Floods, UDP Floods, broadcast storms, and large traffic attacks. It also includes level-based command line protection, allowing different management permissions for various user levels. The switches are equipped with robust security authentication mechanisms such as IEEE 802.1x and RADIUS. They support storm, multicast, and unicast traffic limits to maintain reliable performance in challenging network conditions. Additionally, the ANDA TELECOM series offers an advanced ring detection mechanism for long-term network stability, as well as port isolation within the same VLAN, DHCP Snooping, and IP + MAC + Port binding for enhanced security and control.

Quality of service

ANDA Telecom switches support priority retagging and advanced flow classification based on VLAN, MAC address, source address, destination address, IP, or priority, enhancing the management of carrier services. They offer flexible bandwidth control policies, including port- and flow-based limits, to ensure optimal line speed forwarding on each port. Additionally, these switches support various queue scheduling algorithms such as SP, WRR, and a combination of SP + WRR.

URL: www.andatelecom.com



TECHNICAL SPECIFICATIONS: -

ITEAM	ATS-2900-3200
Interface	8 GE TX ports, 2 100/1000M SFP ports
Console	1 RJ45 port, 1 RST button
Backplane	20 Gbps
Forwarding rate	15Mpps
Power consumption full load	10W
Power supply AC: 100V-240V, 50Hz±10%	15W
Noise@25°C(dBA)	0
MTBF(H)	>50,000
Forwarding mode	Store-forward
MAC	8K
Buffer size (Mb)	4.1
Jumbo frame	9К
Total SVI	10

FEATURES: -

VLAN	 4K Active VLAN QinQ & Selective Quinn GVRP, Private VLAN Voice VLAN
Qos	 CAR, HQoS, MAC/IP/TCP/UDP/ VLAN/COS/DSCP/TOS based QoS,802.1P/DSCP priority relabeling, SP, WRR, and "SP+WRR" Tail-Drop, WRED, flow monitoring and traffic shaping
Spanning Tree	 802.1D (STP) 802.1W (RSTP) and 802.1S (MSTP) BPDU guard, root guard and loopback guard
Multicast	 IGMP v1/2/3 IGMP Snooping IGMP Fast Leave IGMP Filter MVR
■ IP	 Static route IP v4/v6 dual stack DHCP Server/Client/Relay

Anda Telecom Pvt. Ltd.

Registered office: E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366



 Reliability 	 Static/LACP link aggregation, Interface backup EAPS and ERPS ·ISSU
■ Management	 Console, Telenet, SSH, v1/2, HTTP, HTTPS, SNMP v1/v2/v3 RMON TFTP, FTP, SFTP NTP, ZTP SPAN, RSAN
■ Security	 Port isolation, Port security, and "IP+MAC+port" binding, MAC sticky, DHCP Snooping and option 82, DAI & IP source guard, PPPoE+, IEEE 802.1x, Radius and ATTacacs+ L2/L3/L4 ACL flow identification and filtration Anti-attack from DDoS, TCP's SYN Flood, UDP Flood, etc. Broadcast/multicast/unknown unicast storm-control
■ Environment	 Operating temperature/humidity: -10°C-50°C, 10%-90% Storage temperature/humidity: -20°C-70°C, 5%-90% non-condensing
 Certifications 	ISO, IEC, CE, ROHS, TEC, TL-9000

ORDERING INFORMATION: -

Anda Telecom Pvt. Ltd.

Registered Office: PLOT NO 38, BLOCK E, -, Sector 6, Noida, Gautambuddha Nagar, Uttar Pradesh, 201301

India.



https://andatelecom.com/



+91 120 4109590 + 91 98716 50366



info@andatelecomindia.com

Anda Telecom Pvt. Ltd.

Registered office: E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366

 $\textbf{E-mail:} \underline{\textbf{Info@andatelecom.com}} \qquad \textbf{URL:www.andatelecom.com}$