

Model No: AT-OLT-4E16OS2S

Overview

This device provides 16Channel telephone, 1~4Channel E1 interface, 4Channel 10M/100M Ethernet interface (Wire Speed 100M) and 4 expansion interface. 4Channel Ethernet interface is switch interface, can support VLAN. 4 expansion interface can be used as the transmission channel of RS232/RS485/RS422 asynchronous data, voice signal, 2/4 line E&M audio signal, switch signal, Ethernet signal (Bandwidth 2M). It is very flexible.

Product Photo



Features

- Based on self -copyright IC
- E1 interface comply with G.703, adopts digital clock recovery and smooth phase-lock technology Voice port supports FXO and FXS port,
- Support FXO/FXS, EM2/4 audio, Magnet telephone Interface, FXO port docking with program-controlled switchboard, FXS port connected to the user's telephone;
- 1~16channel Voice access, supports caller ID feature and reverse polarity billing functions
- Support various sites mutual number allocation function
- Provide 4 expansion interface, you can extend 1~4Channel asynchronous data, such as RS232/RS485/RS422/Manchester code; 1~4Channel voice, 1~8Channel switch or two/four line audio and so on

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366

E-mail: Info@andatelecomindia.com

URL: www.andatelecomindia.com

- Ethernet interface supports 10M/100M, half/full duplex auto-adaptable, support VLAN
- 4 Channel Ethernet interface is switch interface, support VLAN, can set to 4 channel logical isolation
- Ethernet interface can support AUTO-MDIX (crossed line and straightly connected line self-adaptable)
- Telephone interface with lightning protection, lightning reached IEC61000-4-5 Short circuit current wave 8 / 20 μ s, the peak output voltage 6KV open standards.
- The transmission distance is up to 2-120Km without interruption
- AC 220V, DC-48V, DC24V can be optional

: Parameters

◆ Fiber

Optical port: 1 or 2

Optical Fiber: Single/Dual fiber

Fiber interface: FC/SC/ST/LC(SFP)

Wavelength: 850nm/1310nm Multimode; 1310nm/1550nm Single mode

Relay-free transmission distance: 20~120Km

Typical transmit power:

Single mode 1310/1550nm: ≥ -9 dB

Multimode 850nm: -18dBm

Multimode 1310nm: -25dBm

Receive sensitivity range: -28dBm ~ -40dBm

Physical Interface: RJ45 Support Auto-MDIX

◆ E1 Interface

Interface Standard: comply with protocol G.703;

Interface Rate: n*64Kbps $\pm$ 50ppm;

Interface Code: HDB3;

E1 Impedance: 75 Ω (unbalance), 120 Ω (balance);

Jitter tolerance: In accord with protocol G.742 and G.823

Allowed Attenuation: 0~6dBm

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366

E-mail: Info@andatelecomindia.com

URL: www.andatelecomindia.com

◆ Ethernet interface(10/100M)

Interface rate:	10/100 Mbps, half/full duplex auto-negotiation
Interface Standard:	Compatible with IEEE 802.3, IEEE 802.1Q (VLAN)
MAC Address Capability:	4096
Connector:	RJ45, support Auto-MDIX

◆ FXS Phone Interface

Ring voltage:	75V
Ring frequency:	25HZ
Two-line Impedance:	600 Ohm (pick up)
Return loss:	40 dB

◆ FXO Switch Interface

Ring detect voltage:	35V
Ring detection frequency:	17HZ-60HZ
Two-line Impedance:	600 Ohm (pick up)
Return loss:	40 dB

◆ EM 2/4 Line

AD:	0dB
DA:	-3.5dB
Two/Four-line Impedance:	600 Ohm
Return loss:	20 dB

◆ Working environment

Working temperature:	-10°C ~ 50°C
Working Humidity:	5%~95 % (no condensation)
Storage temperature:	-40°C ~ 80°C
Storage Humidity:	5%~95 % (no condensation)

Specifications

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366

E-mail: Info@andatelecomindia.com

URL: www.andatelecomindia.com

Model	AT-OLT-4E16OS2S
Functional Description	16* telephone, 4E1, 4* FE Ethernet, Console or SNMP, Support 6U rackmount, One or Two Fiber interface, 4*RS232/422/485
Power	Power supply: AC180V ~ 260V ; DC -48V ; DC + 24V Power consumption: ≤10W
Dimension	Product Size: 485X138X45mm(WXDXH) 19 1U
Weight	2.4KG