

AT-AOC-25G-xM

Direct Attach Cable

25/G SFP28 Direct Attach Cable, DAC 1-5m



FEATURES

- Up to 25.88243 Gbps data rate
- Up to 5m transmission
- Hot-pluggable SFP 20PIN footprint
- Improved Pluggable Form Factor(IPF)
- Compliant with enhanced EMI/EMC performance
- RoHS Compliant
- Operating temperature 0° C to +70° C

APPLICATION

25G Ethernet

STANDARD

- Compliant with SFF- 8432 and SFF-8402

General Product Characteristics

SFP28 DAC Specifications	
Number of Lanes	Tx & Rx
Channel Data Rate	25.88243 Gbps
Operating Temperature	0 to + 70°C
Storage Temperature	-40 to + 85°C
Supply Voltage	3.3 V nominal
Electrical Interface	20 pins edge connector
Management Interface	Serial, I ² C

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone : +91 120 4109590, +91 98716 50366


E-mail : Info@andatelecom.com

URL : www.andatelecom.com

High Speed Characteristics

Parameter	Symbol	Min	Typ	Max	Units	Notes
Differential Impedance	Zd	90	100	110	Ω	
Insertion loss	SDD21	8		22.48	dB	At 12.8906 GHz
Differential Input Return Loss	SDD11	12.45		See 1	dB	At 0.05 to 4.1 GHz
	SDD22	3.12		See 2	dB	At 4.1 to 19 GHz
Common Mode Output Return Loss	SCC11	2			dB	At 0.2 to 19 GHz
	SCC22					
Differential Common Mode Output Return Loss	SDD22	10.58		See 3	dB	At 0.01 to 12.89 GHz
	SCD11	12		See 4	dB	At 12.89 to 19 GHz
Differential to common Mode Conversion Loss	SCD21-IL	10			dB	At 0.01 to 12.89 GHz
				See 5		At 12.89 to 15.7 GHz
		6.3				At 15.7 to 19 GHz
Channel Operating Margin	COM	3			dB	

Pin Descriptions



t. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA


Phone : +91 120 4109590, +91 98716 50366

E-mail : Info@andatelecom.com

URL : www.andatelecom.com

Pin	Logic	Symbol	Description
1		VeeT	Module Transmitter Ground
2	LVTTL-O	TX_Fault	Module Transmitter Fault
3	LVTTL-I	TX_Disable	Transmitter disable; Turns off transmitter laser output
4	LVTTL-I/O	SDA	2-wire Serial Interface Data Line (Same as MOD-DEF2 in INF-8074i)
5	LVTTL-I/O	SCL	2-wire Serial Interface Clock (Same as MOD-DEF1 in INF-8074i)
6		Mod_ABS	Module Absent, connected to VeeT or VeeR in the module
7	LVTTL-I	RS0	Rate Select 0, optionally controls SFP+ module receiver
8	LVTTL-O	RX_LOS	Receiver Loss of Signal Indication (In FC designated as Rx_LOS and in Ethernet designated as Signal Detect)
9	LVTTL-I	RS1	Rate Select 1, optionally controls SFP+ module transmitter
10		VeeR	Module Receiver Ground
11		VeeR	Module Receiver Ground
12	CML-O	RD-	Receiver Inverted Data Output
13	CML-O	RD+	Receiver Non-Inverted Data Output
14		VeeR	Module Receiver Ground
15		VccR	Module Receiver 3.3 V Supply
16		VccT	Module Transmitter 3.3 V Supply
17		VeeT	Module Transmitter Ground
18	CML-I	TD+	Transmitter Non-Inverted Data Input
19	CML-I	TD-	Transmitter Inverted Data Input
20		SDA	Module Transmitter Ground

Mechanical Dimensions



Length (m)	Cable AWG
1	30
2	30
5	30/26
7	26

Ordering information

Model No.	Product Description
AT- AOC-25G-xM	25G SFP+ to SFP+ Active Optical Cable 1-100m
x: 001~100 meters	

ORDERING INFORMATION: -

Anda Telecom Pvt. Ltd. Registered Office: PLOT NO 38, BLOCK E, -, Sector 6, Noida, Gautambuddha Nagar, Uttar Pradesh, 201301 India.	  	https://andatelecom.com/ +91 120 4109590 + 91 98716 50366 info@andatelecomindia.com
---	---	--