

AT-QSFPDD-400G-LR4

Optical SFP Module

400G QSFP-DDLR4 Transceiver, SM, LWDM4, 10KM



Features

- Supports 425Gb/s PAM4
- Built-in 400G PAM4 DSP
- Cooled 4 channels EML TOSA
- 4 channels PIN ROSA
- Maximum link length of 10km SMF with KP-FEC
- LC duplex receptacle
- Hot pluggable QSFP-DD form factor
- Digital Diagnostics Monitoring Interface
- Commercial operating case temperature range: 0~ 70° C
- Compatible with RoHS
- Power dissipation <12W
- TDECQ<3.9Db

Application

- 400G Ethernet
- Data Center
- InfiniBand QDR
- Fiber channel

Standard

- IEEE 802.3bs 400GBASE-LR4
- QSFP-DD MSA compliant
- Compliant to SFF-8636

Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Storage Ambient Temperature	TSTG	-40	85	°C
Operating Humidity	HO	5	85	%

Power Supply Voltage	Vcc	-0.3	3.6	V
Signal Input Voltage		Vcc-0.3	Vcc +0.3	V

Recommended Operating Conditions

Parameter	Symbol	Min	Typical	Max	Unit
Operating Case Temperature	Tc	0		70	°C
Power Supply Voltage	Vcc	3.13	3.3	3.47	V
Data Rate, each Lane (PAM4)			106.25		Gbps
Fiber Length 09/125µm core SMF		-	-	10	km

Optical and Electrical Characteristics

Optical Transmitter Characteristics						
Parameter	Symbol	Min	Typical	Max	Unit	Notes
Launched Power (avg.) Per Lane	Pavg	-2.8		5.3	dBm	
Wavelength Range	L1	1294.53	1295.56	1296.59	nm	
Wavelength Range	L2	1299.02	1300.05	1301.09	nm	
Wavelength Range	L3	1303.54	1304.58	1305.63	nm	
Wavelength Range	L4	1308.09	1309.14	1310.19	nm	
Spectral Width(-20dB)	$\Delta\lambda$			0.6	nm	
Extinction Ratio	ER	3.5			dB	
Transmitter OFF Output Power	POff			-30	dBm	
Optical Modulation Amplitude(OMA outer)	OMA	-1.6		5	dBm	
Transmitter and dispersion eye closure(TDECQ)	TDECQ			3.9	dB	
Optical Receiver Characteristics						
Parameter	Symbol	Min	Typical	Max	Unit	Notes
Receiver Wavelength Range	L1	1294.53	1295.56	1296.59	nm	
Receiver Wavelength Range	L2	1299.02	1300.05	1301.09	nm	
Receiver Wavelength Range	L3	1303.54	1304.58	1305.63	nm	
Receiver Wavelength Range	L4	1308.09	1309.14	1310.19	nm	
Average Receiver Power Per Lane		-9.1		4.8	dBm	
Receiver Sensitivity Per Lane	Sen			-7.1	dBm	
Optical Power Input Overload	Pin-max	5.3			dBm	

Receiver Reflectance



Rr

-26

dB

Pin Definitions

Pin Diagram



QSFP-DD MSA-compliant 76-pin connector

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone : +91 120 4109590, +91 98716 50366

E-mail : Info@andatelecom.com

URL : www.andatelecom.com

Pin	Symbol	Name/Description	Notes
1	GND	Ground	1
2	Tx2n	Transmitter Inverted Data Input	
3	Tx2p	Transmitter Non-Inverted Data Input	
4	GND	Ground	1
5	Tx4n	Transmitter Inverted Data Input	
6	Tx4p	Transmitter Non-Inverted Data Input	
7	GND	Ground	1
8	ModSelL	Module Select	
9	ResetL	Module Reset	
10	VccRx	+3.3V Power Supply Receiver	2
11	SCL	2-wire serial interface clock	
12	SDA	2-wire serial interface data	
13	GND	Ground	1
14	Rx3p	Receiver Non-Inverted Data Output	
15	Rx3n	Receiver Inverted Data Output	
16	GND	Ground	1
17	Rx1p	Receiver Non-Inverted Data Output	
18	Rx1n	Receiver Inverted Data Output	
19	GND	Ground	1
20	GND	Ground	1
21	Rx2n	Receiver Inverted Data Output	
22	Rx2p	Receiver Non-Inverted Data Output	
23	GND	Ground	1
24	Rx4n	Receiver Inverted Data Output	
25	Rx4p	Receiver Non-Inverted Data Output	
26	Ground	Ground	1
27	ModPrsL	Module Present	
28	IntL	Interrupt	
29	Vcc Tx	+3.3V Power supply transmitter	2
30	Vcc1	+3.3V Power supply	2
31	InitMode	Initialization mode; In legacy QSFP applications, the InitMode pad is called LPMODE	
32	GND	Ground	1
33	Tx3p	Transmitter Non-Inverted Data Input	
34	Tx3n	Transmitter Inverted Data Input	
35	GND	Ground	1
36	Tx1p	Transmitter Non-Inverted Data Input	
37	Tx1n	Transmitter Inverted Data Input	
38	GND	Ground	1

39	GND	Ground	1
40	Tx6n	Transmitter Inverted Data Input	
41	Tx6p	Transmitter Non-Inverted Data Input	
42	GND	Ground	1
43	Tx8n	Transmitter Inverted Data Input	
44	Tx8p	Transmitter Non-Inverted Data Input	
45	GND	Ground	1
46	Reserved	For Future Use	
47	VS1	Module Vendor Specific 1	
48	Vcc Rx1	+3.3V Power Supply Receiver	2
49	VS2	Module Vendor Specific 2	
50	VS3	Module Vendor Specific 3	
51	GND	Ground	1
52	Rx7p	Receiver Non-Inverted Data Output	
53	Rx7n	Receiver Inverted Data Output	
54	Ground	Ground	1
55	Rx5p	Receiver Non-Inverted Data Output	
56	Rx5n	Receiver Inverted Data Output	
57	GND	Ground	1
58	GND	Ground	1
59	Rx6n	Receiver Inverted Data Output	
60	Rx6p	Receiver Non-Inverted Data Output	
61	GND	Ground	1
62	Rx8n	Receiver Inverted Data Output	
63	Rx8p	Receiver Non-Inverted Data Output t	
64	GND	Ground	1
65	NC	For Future Use	
66	Reserved	Interrupt	
67	Vcc Tx1	+3.3V Power supply transmitter	2
68	Vcc2	+3.3V Power supply	2
69	Reserved	For Future Use	
70	GND	Ground	1
71	Tx7p	Transmitter Non-Inverted Data Input	
72	Tx7n	Transmitter Inverted Data Input	
73	GND	Ground	1
74	Tx5p	Transmitter Non-Inverted Data Input	
75	Tx5n	Transmitter Inverted Data Input	
76	GND	Ground	1

QSFP-DD Module PIN Definition

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone : +91 120 4109590, +91 98716 50366


E-mail : info@andatelecom.com

URL : www.andatelecom.com

Notes:

1. QSFP-DD uses common ground (GND) for all signals and supply (power). All are common within the QSFP-DD module and all module voltages are referred to this potential unless otherwise noted. Connect these directly to the host board signal-common ground plane.
2. VccRx, VccRx1, Vcc1, Vcc2, VccTx and VccTx1 shall be applied concurrently. VccRx, VccRx1, Vcc1, Vcc2, VccTx and VccTx1 may be internally connected within the module in any combination. Each connector Vcc pin is rated for a maximum current of 1000 mA

Mechanical Dimensions



Ordering information

Part. No	Specifications								
	Pack	Rate (Gbps)	Tx (nm)	Po (dBm)	RX	Sen (dBm)	Temp (°C)	Reach (km)	DDM
AT-QSFPDD-400G-LR4	QSFP-DD	400G	EML LWDM	-2.8~5.3	PIN	<-7.1	0~70	10	Y

ORDERING INFORMATION: -

Anda Telecom Pvt. Ltd. Registered Office: PLOT NO 38, BLOCK E, -, Sector 6, Noida, Gautambuddha Nagar, Uttar Pradesh, 201301 India.	  	https://andatelecom.com/ +91 120 4109590 + 91 98716 50366 info@andatelecomindia.com
--	--	--