

AT-500 Series



Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366

E-mail: Info@andatelecomindia.com

URL: www.andatelecomindia.com

SPECIFICATION

Model	AT-500A	AT-500B	AT-500C	AT-500D
Wavelength	1310/1550nm	850/1300nm	1310/1550/1625nm	1310/1550/1650nm
Dynamic range	32/30dB	20/24dB	32/30/30dB	32/30/30dB
Distance setting	Max. 150km	Max. 40km	Max. 150km	Max. 150km
Display	Touch Screen			
Connector	SC/UPC or SC/APC interchangeable adapter		SC/UPC or SC/APC	
Pulse width	SM: 5ns~20us, MM: 5ns~1us			
Event dead zone	1m			
Attenuation dead zone	6m			
OLS function	Same wavelength and connector as OTDR			
OPM function	-50~+26dBm,2.5mm connector, 850/980/1270/1300/1310/1490/ 1550/1577/1625/1650nm			
VFL function	10mW, 2.5mm universal connector			
Storage	Internal memory or TF card(optional)			
Power & Data port	TYPE-C			
Power bank	Type-A 3.7V, 5000mAh			
Operation Temperature	0~+50℃,<90% RH			
Storage Temperature	-20~+70℃,<90% RH			
Size	160*85*38mm			
Weight	About 430g			

ACCESSORIES

STANDARD



Carrying Bag



Manual



Calibration Certificate



AC/DC Adapter
Type -C

OPTIONAL



FCU=FC/UPC
FCA=FC/APC



SCU=SC/UPC
SCA=SC/APC



SCU male-SCA female



LCU=LC/UPC



STU=ST/UPC



SCA male-SCU female

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366

E-mail: Info@andatelecomindia.com

URL: www.andatelecomindia.com