

ATM-101

Optical Power Meter

ATM-101

- ◆ FC, SC, ST adapters and 2.5mm UPP
- ◆ 1000 data storage
- ◆ Data transfer (optional)
- ◆ 7X24 real-time test on PC (optional)
- ◆ Built-in 10mW VFL
- ◆ Energy save mode
- ◆ REF set and dB test
- ◆ 850/1300/1310/1490/1550/1625nm
- ◆ One-year warranty and Three-year recommended calibration interval



CE

Standard



Carrying bag



Calibration certificate



Manual



Packing box

Optional



FC adapter



SC adapter



ST adapter



AC/DC adapter



FC male to LC female adapter



SC male to LC female adapter

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone : +91 120 4109590, +91 93502 57173

E-mail : Info@andatelecomindia.com

URL : www.andatelecom.com

SPECIFICATIONS

Model	ATM-101
Display Range	1310/1490/1550/1625: +10 ~ -70dBm 850/1300: +10 ~ -60dBm
Accuracy *	± 0.2 dB
Calibrated Wavelengths	850nm / 1300nm / 1310nm / 1490nm / 1550nm / 1625nm
Resolution	0.01dB
Connector	FC & 2.5mm UPP (option: SC, ST)
REF	Yes
Automatic Power Off	No operation in 10 minutes (can be cancelled), Low battery energy
Build in VFL	10mW
Data Storage	1000
Battery Charge	For rechargeable battery only
Wave ID	Optional
Data Transfer	Optional
Real Time Monitor	Optional
Battery Life	Above 200 hours
Power Supply	AA * 3 batteries or AC/DC power supply adapter

* at 20±3°C, CW, with FC connector, -5dBm, SM fiber

GENERAL SPECIFICATIONS

Size (H*W*D)	170mm * 97mm * 38mm
Weight	About 380g
Storage Temperature	-20 ~ +60 °C, < 90%RH
Operating Temperature	-10 ~ +50 °C, < 90%RH