

WDM

CCWDM



FEATURES

- ✘ Compact Structure & Package
- ✘ Low insertion loss
- ✘ Low Polarization Dependent Loss
- ✘ High Channel Isolation
- ✘ High Stability & Reliability

APPLICATIONS

- WDM Network
- CATV Network
- PON Network

PERFORMANCE SECTION

Parameter	Unit	Value		
Channel Number	CH	4	8	18

ANDA Telecom Pvt. Ltd.

Registered office: E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone: +91 11 41323629, +91 95 302 57173

E-mail: Info@andatelecomindia.com

URL: www.andatelecomindia.com

Central Wavelength	nm	ITU or ITU+1 (or specified)		
Passband		ITU±6.5		
Product Type	-	Mux or Demux		
Channel Spacing	nm	20		
Insertion Loss	dB	≤1.0	≤1.5	≤3.2
Channel Ripple	dB	<0.5		
Isolation	Adjacent	dB	>30	
	Non-Adjacent	dB	>45	
Directivity	dB	≥50		
Return Loss	dB	≥45		
Polarization Dependant Losses	dB	<0.2		
Polarization Mode Dispersion	ps	<0.1		
Connector		LC/PC、SC/PC、FC/PC or specified		
Operation Temperature	°C	-5~+70		
Storage Temperature	°C	-40~+85		
Package dimension	mm	44×25×6		

Product Series	Function	Channel Spacing	1 st Channel	Fiber Type	Connector	Input/Output Length
C=CWDM	D=Demux M=Mux	4= 4CH	270=1270	0.9A=0.9m m G657A2	LC/UPC LC/APC SC/UPC	05/05= 0.5m
	D&M= Demux & Mux	8=8CH 18= 18CH	290=1290	Rb= Bare fiber	SC/APC FC/UPC FC/APC	10/10= 1m

ANDA Telecom Pvt. Ltd.

Registered office: E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone: +91 11 41323629, +91 95 302 57173

 E-mail: Info@andatelecomindia.com

 URL: www.andatelecomindia.com