



ISO 9001:2000 Certified Comp



AT E205 is an compact office IP phone with rich features. It has 128\*64 HD graphic LCD up to 4-line display; it also has HD Sound Quality, unique art design, demountable bracket to provide multi-angle, 4 programmable keys, an

d friendly user interface to satisfy users's communication needs.

# **Key Features:**

- Support 2 lines;
- Support demountable bracket to provide multi-angle;
- Support 6 programmable keys;
- Support Multi-language, e.g.: Chinese, English, French, Russian, Italian and etc.
- 2\*10/100M Ethernet ports, support POE;
- Auto-provision, HTTP/TFTP/FTP, TR069, PNP;
- Compatible with the platform



ANDA Telecom Pvt. Ltd. ISO 9001:2000 Certified Company

Registered office: E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone: +91 11 41323629, +91 93 502 57173

E-mail: Info@andatelecomindia.com URL: www.andatelecomindia.com





ISO 9001:2000 Certified Company

## **ATE205**

#### **Phone Features**

2 SIP accounts, Hot line
Call hold, Call waiting, Call forward, Call
return; Call transfer (blind/busy/ask)
Caller ID display, Redial, Mute, DND
Auto-answer, 3-way conferencing
Speed dial, SMS, Voicemail
Tone scheme, Volume control
Direct IP call without SIP proxy
Ring tone selection/import/delete
Black list, Hand-free indicator.
Call history: dialed/received/missed (50
-entries);
Soft keys programmable, Supports PC control

Multi-Language:

Chinese,English,French,Russian,Italian,Polish, Portuguesa,Portuguesa-Brasil,Spanish,Turkish

### **Advanced Features**

6 programmable keys

XML Phone Book search and input & output

Enterprise phone book(800 entries)

LDAP phone book

## **IP PBX System Integration**

Busy lamp field (BLF), BLF list
Bridged line appearance (BLA)
DND & Forward synchronization
Intercom, Paging, Music on hold
Call pickup, Dial Plan, Call recording
Anonymous call, Anonymous call rejection
Network conference, Distinctive ring tone

### **Codes and Voice Features**

Wideband Codec: G.722 Narrowband codec: G.711µ/A, G.723.1 G.726, G.729AB,iLBC VAD, CNG, AEC, AGC Full-duplex,

## **Security**

LLDP, VPN(L2TP),802.1x
Transport Layer Security (TLS)
Digest authentication using MD5/MD5-sess
Secure configuration file via AES encryption
Phone lock for personal privacy protection
Admin/User 2-level configuration mode

#### **Network Features**

SIP v1 (RFC2543), v2 (RFC3261)
DNS SRV (RFC3263); IPv6
NAT Traversal: STUN mode
DTMF: In-Band, RFC2833, SIP Info, Auto
HTTP/HTTPS Web Management
IP Assignment: Static/DHCP/PPP0E
Bridge/Router mode for PC port
TFTP/DHCP/PPP0E client
DNS client, NAT/DHCP server

## Management

PNP; SNMP V1/2 , TR069 optional
Configuration:
browser/phone/auto-provision
Trace package and system log export

Auto-provision via FTP/TFTP/HTTP/HTTPS;

## **Physical Features**

128\*64 graphic LCD(Backlight is option)
25 keys, including 4 programmable keys,
2 LEDs: 2\* account lights,
1\* RJ-9 handset port
1\*RJ-9 headset port(Option)
1\*PSTN port(Option)

 $2xRJ45\ 10/100M$  Ethernet ports Power adapter: AC  $100\sim240V$  input and

DC 5V/1A output

Power over Ethernet ,IEEE 802.3af,class

0(Option)

Power consumption: 2.5-3.5W

Net weight: 0.62kg


Dimension: 213\*157\*39mmOperating humidity:  $10\sim95\%$ Storage temperature: up to  $60^{\circ}C$ 

## **Package Features**

Qty/CTN: 10 PCS N.W/CTN: 6.2kg G.W/CTN: 8.5kg

Carton Meas: 430x345x250mm

## Certifications





Registered office: E-36, Amar Colony, Lajpat Nagar-IV, New Delhi - 110024, INDIA

Phone: +91 11 41323629, +91 93 502 57173