

ATE-205



SIP ATE-205

- 2.4 – inch LCD display with backlight
- 2 SIP lines 13 programmable keys
- Optimized noise reduction HD sound quality
- 2.4 G& 5.8G Wi-Fi module is optional
- One-stop remote address book management
- Simple appearance combines elegance and
- Functionality



PRODUCT OVERVIEW: -

ATE-205 series phone, simple design, intuitive operation, redefine enterprise IP communication, designed for small and medium-sized enterprises to create efficient and intelligent communication experience.

ANDA TELECOM[®]

Brightening characteristic

Efficient communication	Dual SIP lines, efficient call management
Clear display	2.4-inch backlit LCD screen for a striking and clear visual experience.
Simple operation	13 programmable keys, simplify the operation process, improve work efficiency.
Smooth collaboration	Support for 5-party conference calls, so that team collaboration is smoother

TECHNICAL PARAMETERS:-

Anda Telecom Pvt. Ltd.
Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA
Phone: +91 120 4109590, +91 98716 50366
E-mail: Info@andatelecom.com URL: www.andatelecom.com

Phone function	• 2 SIP line • Multi-language selection (Chines/ English/ Turkish/ Korean/ Russian/ Traditional Chinese/ French/ Italian/ German/ Portuguese/ Polish/ Thai/ Hindi/ Arabic/ Japanese/ Spanish/ Vietnamese/Persian/Farsi) • Caller ID with display name • Custom DSS key, BLF monitoring, hotline, speed dial • Handle/ hands-free/ headphone mode • Call hold, mute, blind transfer, inquiry transfer • DND, call forwarding, call waiting • Multicast, intercom, text message, keypad lock, emergency call • Direct IP call, redial, callback, auto answer • Five-party conference, line sharing, dialing rules • 10 types of built-in ringtones/ Upload custom ringtones • Manually or automatically synchronize network time • Action URL & Action URI
Audio characteristic	• High-fidelity sound quality : HD handle, HD hands-free • Broadband codec: G.722, Opus • Narrowband codec: G.711(A/μ), G.723.1, G.729AB, G.726, iLBC • DTMF: In-band transmission (In-band) , Out-of-band transmission (RFC 2833), SIP INFO • Full-duplex hand-free • Acoustic echo cancellation (AEC)

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366

E-mail: Info@andatelecom.com

URL: www.andatelecom.com

	• Voice activity detection (VAD) • Comfort noise generation (CNG) • Packet loss compensation (PLC) • Background noise detection (BNE) • Automatic gain control (AGC) • Dynamic adaptive RTP jitter buffer up to 300 MS
Address book	• Blacklist • XML/LDAP address book • Contact smart search • Contact export/ import • Local contacts (1000 entries can be stored) • Call history: dialed/ received/ missed/ forwarded calls (1200 records in total)
IP PBX Features	• BLF, voice message • Anonymous call, anonymous call rejection • Call park, call pickup • Server-based recording function
Configuration and maintenance	• Web configuration, Phone configuration • Automatic deployment: Support FTP/ TFTP/ HTTP/ HTTPS/ SIP PnP/TR-069 • BIN/ CFG configuration • Contact configuration export/ import • CSTA remote control • Network packet capture and diagnosis

Anda Telecom Pvt. Ltd.

Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA

Phone: +91 120 4109590, +91 98716 50366

E-mail: Info@andatelecom.com

URL: www.andatelecom.com

	• CSTA remote control • Netork packet capture and diagnosis • Custom/ full restore factory settings • System firmware upgrade
Network characteristics	• Support IPv4 / IPv6 / IPv4&IPv6 • IP address allocation mode: Static IP / DHCP • Virtual Local Area Network: VLAN • Data link layer protocol: CDP / LLDP • SIP v1 (RFC2543), v2 (RFC3261) • Support redundant servers • Support ICE, STUN (NAT session traversal) • Support UDP/ TCP/ TLS transmission • Support SRTP encryption protocol • SIP trust serve (anti-attack mechanism) • HTTP/HTTPS • TR-069 network management protocol • SNTP automatically synchronizes network dates and times • QoS: QoS: 802.1p/Q tagging (VLAN), Layer3/ ToS/ DSCP • HTTPS certificate management • Support configuration file encryption • Support information verification mechanism

	• RTCP-XR, VQ-RTCPXR , OpenVPN, IEEE802.1X • Wi-F (2.4G&5G) optional
Phone interface	• 1 x RJ-9 (4P4C) handle interface • 1 x RJ-9 (4P4C) headset interface • 2 x RJ-45 10/100M adaptive Ethernet port • DC power interface, USB2.0 interface
Product specification	• Phone main screen: 2.4 inches (132x64) LCD display with backlight • Information indicator: LED red light • Phone keyboard: - 2 SIP line keys (with LED lights, programmable) - 4 customizable soft keys - 12 standard telephone number keys - 6 function keys headset, voice message, mute, call forwarding, redialing, hands-free - 5 navigation keys - 2 volume up/down adjustment keys • Color: business gray • Installation method: Desktop/ Wall-mounted • Desktop size: 187mm*184mm*147mm • IP Phone power consumption: 2~3W • PoE: IEEE 802.3af/IEEE 802.3at • Working environment humidity: 10~95%

	• Working temperature: -10~50° C (+14~122° F)
Carton package	• Packing list: - IP phone: SIP ATE-205 series - Standard Ethernet cable, handle curve - Base, handle and Quick start guide - Power adapter: input AC 100~240V, Output DC 5V / 1000mA • Quantity/ box: 10 units • Gross weight/ carton: 9.5 kg • Color box size: 211 mm×195 mm×100 mm • Carton size: 535 mm×410 mm×230 mm

ORDERING INFORMATION: -

Anda Telecom Pvt. Ltd. Registered office : E-38, Sec 06, Noida, Gautambudha Nagar, Uttar Pradesh - 201301, INDIA Phone : +91 120 4109590, +91 93502 57173	 https://andatelecom.com/  +91 120 4109590, +91 9871650366  info@andatelecom.com
---	---

